



## DIN Dry B -MADE IN EUROPE - Product overview

DIN Dry desiccants are suitable for industrial and military environments.  
 They are produced according to the DIN 55 473, AFNOR NFH 00321 and Military standard MIL-D-3464E.  
 DIN Dry is made from bentonite (dried clay) and available in dust-free tyvec or non-woven fabric wrapping material.



DU <sup>1</sup>	Weight	Product Number	Dimensions	Qty. per sealed pack	Per box	Total qty. Per box	Qty. Boxes per pallet	Qty. Per pallet
1/6	6 g	CBT1/6	70 x 32 x 8 mm	100	15 x 100	1.500	45	67.500
1/3	12 g	CBT1/3	80 x 65 x 8 mm	80	10 x 80	800	45	27.000
1/2	18 g	CBT1/2	85 x 75 x 9 mm	60	10 x 60	600	45	22.500
1	36 g	CBB001	90 x 75 x 10 mm	50	8 x 50	400	45	18.000
2	75 g	CBB002	125 x 100 x 13 mm	30	8 x 30	240	45	10.800
4	150 g	CBB004	155 x 100 x 16 mm	15	8 x 15	120	45	5.400
8	285 g	CBB008	180 x 120 x 20 mm	10	7 x 10	70	45	3.150
16*	590 g	CBB016	210 x 170 x 25 mm	5	7 x 5	35	45	1.575
32*	1.140 g	CBB032	280 x 170 x 40 mm	3	6 x 3	18	45	810

\* Are equipped with hanging cord.

<sup>1</sup> DU: refers to its drying capability, not in volume, and is the amount of desiccant which will absorb at least 6 grams of water vapor at 40% RH at 25°C(77°F).

